



**O'BRIEN**  
 A Product of Hi-Vac® Corporation  
**7030-SC**  
*Hydro***Jetter**  
O'BRIEN MANUFACTURING

**Looks Professional.  
 Performs Like One.**

*This unit is specially designed for the professional day-to-day sewer line cleaner. Municipalities and pumper/cleaner contractors rely on its power and versatility for cleaning a wide range of pipes. The unit has "catwalk" fenders.*

Standard unit color is Safety yellow or white - customer choice. Can be custom painted to match almost any color for an additional charge.

**Available Options**

- \_\_\_\_\_ 100' 3/4" Extra Hose on Main Reel (PNOBJ-100-34AH)
- \_\_\_\_\_ 200' 3/4" Extra Hose on Main Reel (PNOBJ-200-34AH)
- \_\_\_\_\_ Anti-Freeze System (PN OBJ-234)
- \_\_\_\_\_ Arrow Board (PN OBJ-144)
- \_\_\_\_\_ Auto Level Wind Guide Mounted (PNOBJ-9032-34)
- \_\_\_\_\_ Cone Holder Only (PN OBJ-137)
- \_\_\_\_\_ Custom Decals (two)
- \_\_\_\_\_ 80HP John Deere Diesel Engine (PN OBJ-80JDO)
- \_\_\_\_\_ 85HP Cummins Diesel Engine (PN OBJ-85CO)
- \_\_\_\_\_ 110HP Cummins Diesel Engine (PN OBJ-110CO)
- \_\_\_\_\_ E-Stop Assembly (PN IC-100405-01)
- \_\_\_\_\_ Foot Control (PN OBJ-187A)
- \_\_\_\_\_ Garden Hose reel 1/2" - 50' (PN OBJ-123000L)
- \_\_\_\_\_ Garden Hose reel Electric 100' (PN OBJ-294)
- \_\_\_\_\_ Garden Hose reel Manual 100' (PN OBJ-293)
- \_\_\_\_\_ Hose-Reel 42" Weldment (PN J-700-42W)
- \_\_\_\_\_ Hydraulic Surge Brakes (PN 7000SB)
- \_\_\_\_\_
- \_\_\_\_\_ IntelACount® with Parts & Labor (PNOBJ-2430E)
- \_\_\_\_\_ Level Wind Guide w/Counter (PN OBJ-2430A)
- \_\_\_\_\_ Low Water Shutdown (PN OBJ-2424)
- \_\_\_\_\_ Paint Company Color (Paint Code Required)
- STD.** Paint - Safety Yellow (PN PAINT-1Y)
- STD.** Paint - White Enamel (PN PAINT-3W)
- \_\_\_\_\_ Pintle Hitch (PN OBJ-1081P)
- \_\_\_\_\_ Recirculation system (PN OBJ-3/4"RECIRC)
- \_\_\_\_\_ Rotating Beacon-Fixed (PN OBJ-241B)
- \_\_\_\_\_ Side Panels (two) - Painted (PN OBJ-2524P)
- \_\_\_\_\_ Spare Tire Holder w/Tire 16" (PN OBJ-9060-16)
- \_\_\_\_\_ Tank Shroud Aluminum (PN 7000ADS)
- \_\_\_\_\_ Tank Shroud Steel (PN 7000SS)
- \_\_\_\_\_ Wireless Remote (PN OBJ-101)



**Standard Components**

**700 Gallon Polyethylene Tanks**  
 Plate mounted with sump and side baffles  
 Crowned top & side stabilizers for added strength  
 12" Manhole with strainer basket

**"Swinger" Reel—190° Pivot**  
 Makes line cleaning a simple job because it allows for:

- Easy access to the manhole regardless of how trailer is parked.
- Tethered hand operated reel control.
- Variable-speed control.
- Hydraulic driven

**Engine**

Std. 65HP Cummins Diesel Engine  
 Murphy safety gauges with auto-shutdown  
 Variable electronic throttle control

**Triplex Pump - 30 GPM @ 3000 psi**

**Available Accessories**

- \_\_\_\_\_ Cone Safety Red 18" tall (PN OBJ-714)
- \_\_\_\_\_ Fill Hose 25' (PN J-2439)
- \_\_\_\_\_
- \_\_\_\_\_ Grit Catcher 6" (PN OB00016A)
- \_\_\_\_\_ Grit Catcher 8" (PN OB00018A)
- \_\_\_\_\_
- \_\_\_\_\_ Jack Wheel Swivel (PN 80522)
- \_\_\_\_\_ Kit - Emergency Hand Crank (PN OBJ-300)
- \_\_\_\_\_ Lateral Cleaning Kit 150' 3000PSI (PN J-241230)
- \_\_\_\_\_ Manhole Cover Hook (PN 015-438)
- \_\_\_\_\_ Nozzle Extension - Finned 3/4" (PN J-40-5)
- \_\_\_\_\_ Nozzle Extension - NonFinned 3/4" (PN J-40-1)
- \_\_\_\_\_ Rotating Beacon - Magnetic Mount (PN RL650A)
- \_\_\_\_\_ Strobe Light - Magnetic Mount (PN SL650A)
- \_\_\_\_\_ Tiger Tail 3" x 36" (PN J-2203)
- \_\_\_\_\_ Tiger Tail 3" x 42" (PN J-2205)
- \_\_\_\_\_
- \_\_\_\_\_ Tire & Rim 16" Spare (PN J-16614)
- \_\_\_\_\_ Upstream Pulley Guide (PN J-2401)
- \_\_\_\_\_ Washdown Gun w/Hose (PN 15007-B)
- \_\_\_\_\_ Work Light - Magnetic Mount (PNOBJ-500R)

**High-Impact Thermoplastic Sewer Hose**

Easy to keep clean (retains no bacteria-causing residue).  
 Maintains stiffness and is abrasion resistant.  
 Standard 400' hose reaches from manhole to manhole.  
 Reel capacity is 750' of 3/4" hose.

**Tandem-Axle Trailer**

The Trailer Jetter is rated to carry a full tank of water to the job . . .

- 6" channel frame
- A-frame hitch with storage
- 2 5/8" ball hitch (pintle opt.)
- (2) 6,000 lb. DOT-rated axles
- LT245/75R16
- Electric brakes

**Other Standard Components**

Two nozzles: penetrator & flusher  
 Toolbox—integrated enclosed tool & battery storage  
 PVC tank drain valve with stainless steel strainer  
 Direct driven "live" hydraulic system w/17 gal. tnl  
 17-gallon fuel tank with cap-mounted gauge.  
 Air purge system  
 20' Leader hose contrasting color  
 Level wind guide  
 Two (2) aux 12V power supply outlets  
 2" PVC fill pipe

Signature: \_\_\_\_\_

Printed Name: \_\_\_\_\_ Date: \_\_\_\_\_