

# IDEAL FOR UTILITY SERVICE OPERATION INCREASED PRODUCTIVITY LONG SERVICE LIFE



- **=** 6" HIGH CAPACITY VACUUM SYSTEM
- **2,400CFM AND 27" HG VACUUM BLOWER**
- TRIPLEX WATER PUMP: 10 GPM@ 2,500 PSI
- **TOP LOADING 340° BOOM**
- **= 6 CUBIC YARD DEBRIS BODY**
- POWERFUL TRANSFER CASE DRIVE SYSTEM

- POLYGRAPHITE RUST-FREE WATER TANKS (LIFETIME WARRANTY)
- **570-GALLON WATER CAPACITY**
- **CYCLONIC DUST SEPARATORS**
- **OPTIONAL FEATURES:** 
  - **400,000 BTU HEATER**
  - HEATED ENCLOSURE
  - 16" Hg AND 3,400 CFM BLOWER







## X-6 HYDRO EXCAVATOR STANDARD SPECIFICATIONS



#### **DEBRIS TANK**

- 6 vd³ debris tank with dished front head
- Cylindrical design, .312-A-1011 steel, 50,000 PSI minimum yield strength
- Directional splash shield including side shielding attached to tank
- 6" manual gate tailgate drain valve with 6" male cam-lock coupler
- Hydraulically-operated open rear door with 4 hydraulic locks
- Primary shutoff float ball, 10" stainless steel
- · Lifetime debris tank warranty

#### BLOWER

- Roots Model 616 DVJ vacuum pump capable of producing 2400 CFM and 27" Hg
- Blower drive via OMSITransfer Case
- Strainer housing with O-ring seal
- Level 5 Ultra Quiet Exhaust Silencer with up and away design
- Hi-Vac standard final 85 micron blower inlet filter, removable and cleanable
- 8" air-operated vacuum relief valve

#### **WATER TANKS**

- Polygraphite rust-free water tanks (lifetime warranty)
- Side-mounted water tanks total 570 gallons (larger capacity available)
- 2" water fill line with anti-siphon device and 2-1/2" coupling
- Poly tank butterfly check valve on top of the front tank for fill hose access

#### **WATER PUMP**

- Adjustable Triplex water pump: 0-10 GPM; 0-2500 PSI
- Water pump water volume is set independently of blower speed and remains at set-point via pneumatic unloader valve

#### **HOSE REEL SYSTEM**

• Spring loaded hose reel: 1/2" x 100' high-pressure hose with swivel 1/2" male fitting on each end-mounted curb side of unit

#### CYCLONE SEPARATOR

Cyclone separator collection chamber with cleanout

#### TOP HYDRAULIC LOADING BOOM

- 340° hydraulic rotation
- •Turret bearing style with accessible grease fitting on top
- 6" heavy-duty wire reinforced rubber suction hose
- Boom is power up/down, right/left, extend/retract
- Boom inlet box cleanout and inspection port

#### **CONTROL PANEL**

- Mounted on curb side of unit
- Controls mounted in a NEMA 4 enclosure
- Tachometer, vacuum gauge, water pump pressure gauge, hydraulic loading boom, vacuum relief valve, tailgate functions and work lights

#### LIGHTING

• LED DOT lighting with 2-light rear module assembly, clearance lamps, reflectors and 3-light center marker

#### **COLD WEATHER PACKAGE**

Air purge system with coiled air hose

#### **VACUUM TUBE PACKAGE**

- 1 6" x 6' aluminum tube
- 1 6" x 6' aluminum tube w/ rubber dig end
- 2 6" coupling clamps

#### **TOOL PACKAGE**

• 1 pistol type handgun assembly with digging wand and

#### **REAR BUMPER**

Standard frame-mounted tubular design

#### **PAINTING**

• Sandblasted white w/ 2 coats primer and 2 coats single color urethane paint. All painting done prior to final assembly.

- Single axle diesel-powered truck chassis
- · Chassis engine powers the system

#### **ADDITIONAL FEATURES**

- Frame-mounted ground cable reel
- 4-tube mounted rack on tailgate

### **AVAILABLE OPTIONS**

#### WIRELESS CONTROL OPTION

- 16-function wireless remote control
- · Back-up remote and in-cab charger

#### **HEATED EQUIPMENT ENCLOSURE**

- Custom fabricated steel enclosure with access doors
- Access steps on each side
- Heater with thermostat

#### **BLOWERS**

• 16" Hg and 3400 CFM Blower

#### LIGHTING

- Work light package
- Strobe lights (cab and/or module)
- Arrow boards

#### **HOT WATER HEATER**

• 400,000 BTU heater, 12 Volt DC controls

#### **AIR KNIFE SYSTEM**

• Air 350 CFM @ 150 psi option available

A FAMILY COMPANY SINCE 1967



CORPORATE HEADQUARTERS
4713 Gettysburg Rd | Mechanicsburg, PA 17055 📞 800.626.7835 🏻 sweeperland.com