



# SuperVac *Super* Updraft™

3 Cubic Yard Low Profile Parking Area Sweeper



MADE IN THE USA

\*Sweeper shown with optional equipment

- Vertical Digger Broom
- WhisperWheel Fan Technology
- Full Size Sweeping Head
- Stainless Steel Welded Construction
- Large Water Capacity
- Optional Curb Blower Available

800.879.7933

[www.schwarze.com](http://www.schwarze.com)

# SuperVac Super Updraft

<b>CHASSIS</b>		<b>DEBRIS HOPPER:</b>		<b>OPTIONAL WATER SYSTEM:</b>	
Model / type	NPR Gas	Volumetric capacity	3.0 cu yd (2.3 cu m)	Type	Diaphragm
Manufacturer	Isuzu	Dumping	Hydraulic high dump	Tank capacity	25 gal (96 l)
Engine	GM V8 Vortec 6.0 Liter	Material	Stainless steel	Construction	Polyethylene
Fuel	Gas, 30 Gal In Frame Tank	Dump height	69 in (1753 mm)	Pump	Electric 12 V dc
Air filter	Dry type; heavy duty	Dumping tilt angle	88°	Controls	Electric; in-cab
Standard GVWR	12,000 lb (5,443 kg)*	Inspection doors	1 on left side 1 on right side	Filter	100 mesh screen
Optional GVWR	14,500 lb (6,577 kg)**	Controls	Electric; in-cab	Mounting	Removable
Transmission	6L90 6 speed automatic	Paint	Imron Elite®	Fill diameter	3 in (76.2 mm)
Tires	(6) Tubeless steel-belted radials	<b>ELECTRICAL SYSTEM:</b>		Nozzles	2 on broom; 2 inside hopper
* 12,000 GVW	215/85R16E (10-ply)	Battery	1 @ 12 V, 750 cca each	Optional	Front spray bar
** 14,500 GVW	225/70R19.5G (14-ply)	Controls	Electric; in-cab	<b>SIDE BROOM:</b>	
Wheels	Steel construction	Circuit protection	Resettable circuit breakers	Type	Vertical digger
Steering	Integral power;	Rear view camera	Color; dash mounted	Bristle	Wire or poly
Brakes	Vacuum/hydraulic with 4-channel ABS	<b>FAN SYSTEM:</b>		Diameter	26 in (660 mm)
<b>GENERAL SPECIFICATIONS:</b>		Type	Whisper wheel turbine	Drive	Hydraulic torque motor
Wheelbase	133 in (3378 mm)	Drive	Belt driven	Speed	Variable
Sweeping width	81 in (2057 mm)	Number of blades	10	Mounting	Trailing arm design
With one gutter broom option	94 in (2388 mm)	Diameter	24 in (610 mm)	Location	Left hand side
Turning radius	274 in (6960 mm)	Construction	Welded abrasion-resistant steel	Suspension	Free floating
Overall length	230 in (5842 mm)	Housing liner	Bolt-in corded rubber	Wear adjustment	Automatic
Overall height (without beacon)	82 in (2083 mm)	Mounting	Pillow block bearings	Impact protection	Spring
Overall width	89 in (2261 mm)	Vacuum enhancer	For heavy/light material	Tilt angle adjustment	Manual; at broom
<b>AUXILIARY ENGINE:</b>		<b>PICKUP HEAD:</b>		<b>HYDRAULIC SYSTEM:</b>	
Manufacturer	B&G Vanguard Big Block	Type	Debris-moving blast and suction	Type	Belt driven gear pump
Horse power	25	Operating direction	Forward and reverse	Fluid capacity	3 gal (11.4 l)
Type	Air cooled gasoline	Suspension	2 trailing arms; 4 springs balanced	Purpose	Power gutter broom
Air cleaner	Centrifugal multi-stage	Length	80 in (2032 mm)	Dump system hydraulics	12 V power unit, 1 gal (3.8 l)
Cylinder	Cast iron cylinder sleeve	Pressure hose diameter	10 in (254 mm)	<b>OPTIONAL EQUIPMENT:</b>	
Warranty	3 year	Suction hose diameter	10 in (254 mm)	Polyethylene tool box	
		Flap design	3 flaps	Rear trash bag rack	
		Controls	Hydraulic raise and lower	Cab mounted strobe	
		Skids	Tungsten carbide	Extra flood light	
				Curb blower.	

Note: design and specifications subject to change without notice.

Schwarze parking lot sweepers are guaranteed to be free from defects due to faulty materials and/or workmanship for a period of 12 months, or 1200 hours. Liability is limited to replacement or repair of defective part(s) at factory or authorized dealer. The standard warranties of the chassis and auxiliary engine manufacturer shall apply.

Also Available from Schwarze Industries, Inc:



A FAMILY COMPANY SINCE 1967

**Bortek**  
INDUSTRIES, INC.

**WE KNOW CLEAN**

800.626.7835 BORTEKINDUSTRIES.COM

Affiliates:



© 2022 Schwarze Industries  
1055 Jordan Road  
Huntsville, AL 35811  
800.879.7933  
An Alamo-Group Company

